



Installation advice

How does it work and what should I keep in mind when drying?

If you have rented a dehumidifier, possibly in combination with a fan and/or heater, to speed up the drying process, there are a few tips and points worth knowing that will help you achieve a faster drying result.

Installing the dehumidifier

Preferably place the dehumidifier in a central location in the room that needs to be dried, and (if available) near a drain. Place the dehumidifier at least 40 cm away from the wall, with the air outlet (the round opening) pointing towards the centre of the room. Place the hose of the dehumidifier in a drain or in a large bucket. Always make sure the hose cannot fall out of the drain or bucket. Plug the unit into the socket and switch it on by pressing the red  button on the display.

Installing the fan

Place the fan(s) in the room to be dried. Position the fan on one side of the room and aim it so that the air is blown across the wet surface towards the other side of the room. If you have applied plasterwork that needs to dry, aim the fan (from a distance) at the wall to be dried. For an optimal and even drying process, you can move the fan(s) daily by pointing them in a different direction. Make sure all parts of the floor or wall are properly ventilated for a fast drying result.

Vacuum the floor with an (industrial) vacuum cleaner. This ensures that the pores of the floor are not clogged with dust. It promotes the drying process and prevents dust from being blown up into the room.

You will achieve the best drying results at a temperature between 15 and 25 degrees Celsius.

If you use an extension reel or extension cable, it must be sufficiently thick.

Important!

Always fully unwind extension reels!

If this is not done, there is a risk of fire.

Worth knowing

- The top layer of anhydrite floors often retains moisture, which can slow down the drying process. If you have an anhydrite floor in your home, we recommend sanding off the top layer of the floor (preferably with a diamond grinder). This significantly speeds up the drying process. By sanding the top layer, moisture can evaporate more easily.
- Close windows and (exterior) doors. This prevents humid outdoor air from entering. Close the doors of rooms that do not need to be dried.
- To determine whether the moisture content is low enough for further finishing with your final floor, a moisture measurement should be carried out. For warranty reasons, preferably have this done by your flooring company.

For other questions, you can also check the FAQ ("veel gestelde vragen") on our website bouwdroger-huren.nl.

Cancellation and return

If you want to use the dehumidifier for longer than originally booked on our website, that is of course possible. Four days before the booked collection day, you will receive an email from us with a telephone number you can call to let us know that you want to use the drying equipment for longer. We ask you to contact us at least 72 hours (3 days) before the collection day, so that we can cancel or change the return transport free of charge.

If you cancel or change the collection within 72 hours, 50% of the transport costs will be charged.

If the cancellation or change of the return transport takes place within 24 hours, 75% of the transport costs will be charged.